



MOBILE CABLE WINDER MW 800

Cable winding on cable reels or cable coils



FEATURES

- High degree of flexibility and winding power
- Cables with diameters up to 40 mm can be rewound easily and quickly from reel rack systems or a reel stand
- The ground-level pick-up of cable reels or drums enables a rational and safe rewinding process
- A plug-in coil winding unit for quick changeover for cable coils and an automatic laying for longer cable lengths is optionally available

TECHNICAL DATA

Performance	Winding coils	Winding cable reels
Inner diameter / Core diameter	450 mm	100 mm
Outer diameter	750 mm	up to 800 mm
Coil height	approx. 50 - 200 mm	
Max. drum width Min. drum width		660 mm (675,2 mm clear distance) 100 mm (87,2 mm clear distance)
Flexible cable up to diameter	max. 45 mm	max. 45 mm
Weight cable coils / cable reels	40 kg	300 kg
Speed	up to 3 m/s	up to 3 m/s
Control system	PLC and LCD operating terminal. Programmable are: Inner and outer diameter. Laying gradient	
Revolution	max. 200 min.-1	max. 200 min.-1
Optional	Automatic laying	Automatic laying
Special	Mobile device with ground level pick-up / set down of cable reels and cable coils directly from the floor	

LOCATION SWITZERLAND

Ramatech Systems AG . Hohenrainstrasse 36 . CH - 6280 Hochdorf
Phone: +41 41 914 26 26 . E-Mail: info@ramatech.ch

© Ramatech systems 2023

LOCATION GERMANY

Ramatech Systems GmbH. Messerschmittstraße 30 . D - 89231 Neu-Ulm
Phone: +49 731 40 199 200 . E-Mail: info@ramatech.de